



ICOTA8 第8届国际最优化方法及应用大会

The 8th International Conference on Optimization:
T Techniques and Application **S**

December 10–13, 2010
Shanghai
Fudan University

Book of Abstracts



Editors: Xiaoling Sun, Xiaodi Bai
© Fudan University. All rights reserved.

Convergence Analysis of an Explicit Exchange Method for Convex Semi-infinite Programming Problems with Second-order Cone Constraints	
Shunsuke Hayashi*, Soon-Yi Wu, Liping Zhang	88
A New Exchange Method for Convex Semi-infinite Programming	
Liping Zhang*, Soon-Yi Wu, Marco A. López	90
On Saddle Points in Nonconvex Semi-infinite Programming	
Jan-J. Rückmann*, Francisco Guerra-Vázquez, Ralf Werner	91
A Regularized Explicit Exchange Method for Semi-infinite Programs with an Infinite Number of Second-order Cone Constraints	
Takayuki Okuno*, Shunsuke Hayashi, Masao Fukushima	92
An Algorithm for Semi-infinite Transportation Problems	
Soon-Yi Wu*, Shen-Yu Chen	94
Relaxed Cutting Plane Method with Convexification to Solve Nonlinear Semi-infinite Programming Problems	
Ting-Jang Shiu*, Soon-Yi Wu	95
Experiences with Reduction Method to Solve Semi-infinite Programming Problems	
Ana I. Pereira*, Edite M.G.P. Fernandes	96
Capacity-achieving Probability Measure in Communication Channels	
Satoshi Ito*, Shiro Ikeda	98
A Smoothing Penalized Sample Average Approximation Method for Stochastic Programs with Second Order Stochastic Dominance Constraints	
Hailin Sun*, Huifu Xu, Yong Wang	99
Inertial Relaxed CQ Algorithm for Solving Split Feasibility Problem	
Yazheng Dang*, Yan Gao, Jin Dong	101
Nonlinear Extension of Multi-objective Multiclass Support Vector Machine Maximizing Margins Based on One-against-all Method	
K. Tatsumi*, M. Tai, T. Tanino	103
Global Quadratic and Polynomial Optimization (SS01)	
Quadratic Optimization under Uncertainty with Applications	
V. Jeyakumar	105
Semi-algebraic Geometry and Global Optimization Problems with Polynomial Constraints	
Guoyin Li	106
On Stability Results for Quadratic Optimization Problems	
Gue Myung Lee*, Nguyen Nang Tam, Nguyen Dong Yen	107
Solving Large-sized Sensor Network Localization Problems using Sparsity and Continuation	
Sunyoung Kim*, Masakazu Kojima	108
Combinatorial Optimization-Theory and Applications (SSM04-A ~ SSM04-B)	
The Backup 2-Median Problem on Block Graphs	
Yukun Cheng*, Liying Kang, Yan Hong	110
A Lower Bound of Some Classical Ramsey Numbers $R(3, t)$	
Decha Samana*, Vites Longani	112
The Hamiltonian Cycle Problem and Some Challenging Non-Convex Programs	
Jerzy A. Filar	113

Experiences with reduction method to solve semi-infinite programming problems

Ana I. Pereira

*Department of Mathematics - ESTiG, Polytechnic Institute of Braganca,
Campus de Sta Apolónia, 5301-854 Braganca, Portugal
apereira@ipb.pt*

Edite M.G.P. Fernandes

*Department of Production and Systems, University of Minho,
Campus de Gualtar, 4710-057 Braga, Portugal
emgpf@dps.uminho.pt*

Abstract

In this talk, some variants of reduction-type method combined with a line search filter method to solve nonlinear semi-infinite programming problems are presented. We use the stretched simulated annealing method and the branch and bound technique to compute the maximizers of the constraint. The filter method is used as an alternative to merit functions to promote convergence from poor starting points.

Keywords: Semi-infinite programming. Reduction method, Line search filter method.

1 Introduction

The semi-infinite programming (SIP) problem is considered to be of the form

$$\min f(x) \text{ subject to } g(x, t) \leq 0, \text{ for every } t \in T \quad (1)$$

where $T \subseteq \mathbb{R}^m$ is a nonempty set defined by $T = \{t \in \mathbb{R}^m : a \leq t \leq b\}$. Here, we assume that the set T does not depend on x . The nonlinear functions $f : \mathbb{R}^n \rightarrow \mathbb{R}$ and $g : \mathbb{R}^n \times T \rightarrow \mathbb{R}$ are twice continuously differentiable with respect to x and g is continuously differentiable functions with respect to t .

There are many problems in the engineering area that can be formulated as SIP problems. For a review of some applications, the reader is referred to [9, 5, 10].

The numerical methods that are mostly used to solve SIP problems generate a sequence of finite problems. Some examples can be found in [9, 2, 3, 4, 8, 10].

This work aims to describe a reduction method for SIP. Conceptually, the method is based on the local reduction theory. The focus of our proposal is to compare the performance of some methods in global programming theory: the simulated annealing method and the branch and bound method. This work comes in the sequence of a previous reduction-type method presented in [6].

2 Reduction method

A reduction approach, based on the local reduction theory, describes the feasible set of the SIP locally by finitely many inequality constraints. Thus, the SIP problem can be locally reduced to a finite one (at least conceptually, see [4]). Given a feasible point $x_k \in \mathbb{R}^n$, consider the so-called lower level problem $O(x_k)$:

$$\max_{t \in T} g(x_k, t), \quad (2)$$

where $T_k = \{t_1, \dots, t_{L_k}\}$ is the set of its local solutions satisfying the following condition

$$|g(\bar{x}, t_l) - g^*| \leq \delta^{ML}, \quad l = 1, \dots, L_k, \quad (3)$$

where L_k represents the cardinality of T_k , δ^{ML} is a positive constant and g^* is the global solution value of (2).

Under some conditions, it is possible to replace the infinite set of constraints by a finite set that is locally sufficient to define the feasible region. Thus the problem (1) is locally equivalent to the so-called reduced optimization problem

$$\min_{x \in U_k} f(x) \text{ subject to } g_l(x) \equiv g(x, t_l(x)) \leq 0, l = 1, \dots, L_k. \quad (4)$$

where U_k is a open neighborhood of x_k .

A reduction method then emerges when any method for finite programming is applied to solve the locally reduced problem (4). Thus, at each iteration k , the main procedures of the algorithm are:

1. based on an approximation to the SIP problem, x_k , compute the set T_k , solving problem (2), with condition (3);
2. based on the set T_k , implement at most i^{\max} iterations to get an approximation $x_{k,i}$, by solving the reduced problem (4);
3. use a globalization technique to compute a new approximation x_{k+1} that improves significantly over x_k ;
4. use termination criteria to decide if the iterative process should terminate.

The remaining part of this work presents our proposals for the four steps of a global reduction method for SIP. An algorithm to compute the set T_k is known in the literature as a multi-local procedure. Our proposals are the stretched simulated annealing method and branch and bound method. To solve the reduced problem (4) an interior point method is proposed. Finally, convergence of the overall reduction method to a SIP solution is encouraged by implementing a filter line search technique.

References

- [1] R. Hettich and K.O. Kortanek, *Semi-infinite programming: Theory, methods and applications*, SIAM Review, 35, (1993), pp. 380–429.
- [2] D-H. Li, L. Qi, J. Tam, and S-Y. Wu, *A smoothing Newton method for semi-infinite programming*, Journal of Global Optimization, 30 (2004), pp. 169–194.
- [3] C. Ling, Q. Ni, L. Qi, and S-Y. Wu, *A new smoothing Newton-type algorithm for semi-infinite programming*, Journal of Global Optimization, 47 (2010), pp. 133–159.
- [4] G-x. Liu, *A homotopy interior point method for semi-infinite programming problems*, Journal of Global Optimization, 37 (2007), pp. 631–646.
- [5] M. López, G. Still, *Semi-infinite programming*, European Journal of Operations Research, 180, (2007), pp. 491–518.
- [6] A.I.P.N. Pereira and E.M.G.P. Fernandes, *A reduction method for semi-infinite programming by means of a global stochastic approach*, Optimization, 58, (2009), pp. 713–726.
- [8] L. Qi, C. Ling, X. Tong, and G. Zhou, *A smoothing projected Newton-type algorithm for semi-infinite programming*, Computational Optimization and Applications, 42 (2009), 1–30.
- [9] R. Reemtsen and J.-J. Rückmann, *Semi-infinite programming*, Nonconvex Optimization and Its Applications, Vol 25, 1998, Kluwer Academic Publishers.
- [10] O. Yi-gui, *A filter trust region method for solving semi-infinite programming problems*, Journal of Applied Mathematics and Computing, 29 (2009), pp. 311–324.